BL003 Carbide Tipped Band Saw Blade

> Creation Date: September 11,2008 Revision Date: February 21,2013

Safety Data Sheet

1. IDENTIFICATION

CARBIDE TIPPED BAND SAW BLADE **Product Name**

For a metallic material cutting

SDS BL003 Serial No. Corporate Name AMADA CO.,LTD.

Address 56 Hata-machi, Ono-shi, Hyogo, Japan

Department Technical Administration DEPT. Quality Control Gr.

Person in charge Katsumasa Yoshida Phone No. +81 794-62-5931 FAX No. +81 794-62-4351

2. HAZARDOUS INGREDIENTS

Carbide Tipped band saw blade is physically and chemically steady in the solid condition.

Carbide Tipped band saw blade has neither physical and chemical hazards nor environmental hazards.

Each alloy elements are related to hazardous to human health and hazardous top the aquatic environmental.

If dust stored in a dry condition or stored with oil, those would be ignitable.

However, subsequent operations such as grinding, welding and melting, cause a release of dust or fumes which may cause some of the ingredients it change to a form which could affect workers.

[GHS CLASSIFICATION]

HEALTH

PHYSICAL Explosives : Not applicable

HAZARDS Flammable gases : Not applicable

Flammable aerosols : Not applicable Oxidizing gases : Not applicable Gases under pressure : Not applicable Flammable liquids : Not applicable Flammable solids : Not classified Self-reactive substances and mixtures : Not applicable Pyrophoric liquids : Not applicable Pyrophoric solids : Not classified

Self-heating substances and mixtures : Not classified Substances and mixtures which,in contact witl : Not classified

water, emit flammable gases contact with water Oxidizing liquids

: Not applicable Oxidizing solids : Not applicable Organic peroxides : Not applicable Corrosive metals : Not classified : Not classified Acute toxicity(oral) Acute toxicity(skin) : Not classified

HAZARDS Acute toxicity(inhalation) : Not classified Skin corrosion/irritation : Category 3

(Symbol: none, Signal word: Warning)

Serious eye damages/eye irritation : Category 2B

(Symbol: none, Signal word: Warning)

Respiratory sensitization : Category 1

(Symbol: health hazard, Signal word: Danger)

Skin sensitization : Category 1

(Symbol: exclamation mark, Signal word: Warning)

Germ cell mutagenicity : Category 2

(Symbol: health hazard, Signal word: Warning)

Carcinogenicity : Category 1B

(Symbol: health hazard, Signal word: Danger)

Reproductive toxicity : Category 1B

> (Symbol: health hazard, Signal word: Danger) : Category 1 [respiratory organs • kidney]

Specific target organ toxicity (single exposure) (Symbol: health hazard, Signal word: Danger)

Category2[Systemic toxicity]

(Symbol: health hazard, Signal word: Warning) Category3[Respiratory tract irritation]

(Symbol: exclamation mark, Signal word: Warning) : Category1[respiratory organs • nervous system] (Symbol:health hazard, Signal word:Danger)

Aspiration hazard : Not classified

Specific target organ toxicity

(repeated exposure)

1/5

: Not classified : Category4

(Symbol:none, Signal word:none)

[GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS]

SYMBOL





SIGNAL WORD : Danger

HAZARD : Causes skin irritation
STATEMENT : Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause allergy skin reaction May cause a hereditary disease

May cause cancer

May have harmful effects on reproductive competence and fetus Disorder of the respiratory system and damage to the kidney

May be associated systemic toxicity

Fear of stimulation to airway

Disorder of the respiratory system and nerve damage Fear of harmful for aquatic organism by long term effect

PRECAUTIONARY STATEMENT:

[Safety measure]

Protector

Employees should wear the mask approved respiration and full protective clothing for protection against heavy concentration of dust or fumes.

And also employees should wear gloves, hard hat, protective shoes and leg protector.

Approved safety glasses with side shields, or goggles, should be worn.

Approved protective filters for the mask.

Employees do not eat and drink while operating.

Remove extraneous matter from working clothes and wash hands after operation.

[EMERGENCY FIRST AID]

Inhalation : Remove to fresh air, if condition continues consult

Eye Contact : Flush well with running water, get medical attention.

Ingestion : Seek medical help

【STORAGE】 Keep it indoor.If you keep it outdoor, avoid a thing and a dewfall

wet by rain, the snow, and the fog.

Keep it in the place where child's hand doesn't reach.

【DISPOSAL】 Follow federal, state and local regulations regarding disposal.

3. ALLOYING ELEMENTS, BASE METAL ALLOYING ELEMENTS

Coated substance TiN TiAIN

Classification of Substance and Mixture
Chemical or generic name

Element and content

CAS No.

PRTR No.

Table—1 • 2

Industrial Safety and Health Act No.

Mixture

Metallic alloy

Table—1 • 2

Table—1 • 2

Table—1 • 2

Table—1 • 2

Table - 1

	Cemical Combosition					
	Elements	Symbol	CAS No.	Cabinet order No	Industrial Safety and Health Act No.	Content (mass%)
Tooth Edge	Tungsten Carbide	WC	12070-12-1	_	1	90~94
100th Eage	Cobalt	Со	7440-48-4	1-132	table9-172	6 ~ 10

^{*}The above-mentioned material doesn't correspond to a poison, a deleterious substance, and a specific deleterious substance in Deleterious Substance Control Law.

						Table 2
	Cemical Combosition					
	Elements	Symbol	CAS No.	Cabinet order No	Industrial Safety and Health Act No.	Content (mass%)
	Silicon	Si	7440-21-3	_	_	0.1~0.5
	Manganese	Mn	7439-96-5	1-412	table9-550	0.1~0.6
	Nickel	Ni	7440-02-0	1-308	table9-418	0~0.7
	Chromium	Cr	7440-47-3	1-87	table9-142	1~5
Backing Material	Tungsten	W	7440-33-7	_	table9-337	0~0.1
	Molybdenum	Мо	7439-98-7	1-453	table9-603	1~4
	Vanadium	V	7440-62-2	_	_	0.1~0.4
	Cobalt	Со	7440-48-4	1-132	table9-172	none
	Iron	Fe	7439-89-6	_	_	residual quantity

^{*}The above-mentioned material doesn't correspond to a poison, a deleterious substance, and a specific deleterious substance in Deleterious Substance Control Law.

4. EMERGENCY FIRST AID

Subsequent operations such as grinding and welding cause a release of dust or fumes which may cause some of the ingredients it change to a form which could affect workers.

Inhalation : Remove to fresh air, if condition continues consult

Eye Contact : Flush well with running water more than 15 minutes, get medical attention.

Ingestion : Seek medical help

Acute symptom: There is a possibility of angry when catching one's eye.

There is a possibility of becoming unpleasant when sucking.

Symptom : There is a possibility of vomiting when swallowing.

5. FIRE FIGHTING MEASURES

Extinguishing media : Unrestricted

Fire : If dust stored in a dry condition or stored with oil, those would be ignitable.

Wear full body protective clothing with breathing apparatus and safety shoes.

Extinguishing media: Powder for metal or dry sand.

Do not pour water, heating may cause hydrovolcanic explosion.

It is acceptable to pour water to be lower temperature in unburned area.

6. SPILLS AND LEAKS

Stems to take in case of release or spill: none

Notes of human body: Employees should wear approved protector for preventing of inhalation

and entering the eyes of dust.

Notes of environment: Collect dust as much as possible.

Disposal method: It is the most preferable to clean up the dust by cleaner.

Dust is wiped off with the wet mop.

7. CAUTION FOR STORAGE AND HANDLING

Handling : Employees should wear approved respirators and full protective clothing and mask

Technological for protection against heavy concentration of dust and fumes.

countermeasure : Employees should wear protective glasses.
Employees should wear gloves when handling.

Operating suggestions: Do not throw a product.

Do not handling it leads to electric shock.

Storage Keep it in case until just before operation for prevention rust of product.

Technological countermeasure: Do not put product on wet floor while in use.

Storage condition: The transformation of the product is avoided.

The tier of the product is avoided.

The place of the high temperature, and humidity is avoided.

3/5

8. SPECIAL PROTECTION INFORMATION

Facilities : Set up the local exhaust ventilation.

The dust mask is worn if necessary when there is a possibility to exceed

the density of the allowance.

Washing place for eyes is set up near handling place.

Working environment permissible exposure limit

·		*OSHA PEL	* * ACGIH TLV	Japan Association of Industrial Health
Alloying Elements	Symbol	mg∕ mื	mg∕ m ឺ	permissible concentration
		(metal dust density)	(metal dust density)	mg/mឺ
Iron	Fe	* * * N/A	N/A	N/A
Silicon	Si	15	10	N/A
Manganese	Mn	5	0.2	0.3
Nickel	Ni	1	1.5	1
Chromium	Cr	0.5	0.5	0.5
Molybdenum	Мо	15	10	N/A
Tungsten	W	N/A	5	N/A
Vanadium	V	N/A	N/A	N/A
Cobalt	Co	0.1	0.02	0.02

*OSHA : Occupational Safety and Health Administration

PEL : Permissible exposure limit

**ACGIF: American Conference of Governmental Industrial Hygienists

TLV : Allowable limit ***N/A : Not Applicable

Protection

Respiratory protection : Wear applicable dust mask or protector of respiration.

Hands protection : Suitability and durability of glove type is dependent on usage.

Eyes protection : Safety glasses

Sanitary requirement : Recommend the local exhaust ventilation. Wash hands before smoking

and after operation.

9. PHYSICAL DATA

Physical condition Table - 3 Color Metallic color Table - 3 Odor PΗ **Boiling Point** Melting Point Table - 3 Flash Point none Explosion limit Vapor Pressure Table - 3 Ratio Solubility in Water Table - 3 Octanol-water partition coefficient Spontaneous ignition temperature Decomposition temperature Volatile none

Table - 3	
-----------	--

	Physical condition	Solid Metal
	Odor	Odorless
	Boiling Point	_
Physical and	Melting Point	1490°C(part of carbide tip : 2868°C)
Chemical data	Solubility in Water	Insoluble
	Vapor Density	_
	Vapor Pressure	_
	Ratio	7. 9(part of carbide tip:14. 9)

10. REACTIVITY DATA

Stability : Chemically stable.

Incompatibility: Reacts with strong acid to generate hydrogen gas.

11. HEALTH HAZARD STATEMENT

Steel products in the from shipped do not present a health hazard. However, subsequent operations such as grinding, welding and melting ,cause a release of dust or fumes which may cause some of the ingredients it change to a form which could affect workers.

No evaluation data and hazardous information for skin corrosion, irritating nature, skin sensitizer,

eye irritancy, germ cell mutagenicity, reproductive toxicity, carcinogenicity.

No hazardous information for specific target internal organs toxicity

No information for special target organ toxicity, aspiration hazard and harmful effect.

12. ENVIRONMENTAL IMPACT

No information for environmental effect.

13. DISPOSAL METHOD

Follow federal, state and local regulations regarding disposal. Use as recycled material as possible.

14. TRANSPORTATION

International regulation

Sea restriction Nonhazardous material (except Metallic powder)

Marine Pollutant Not applicable

Airlines restriction Nonhazardous material (except Metallic powder)

Domestic regulation

Land restriction Not applicable (except Metallic powder)

Sea restriction Nonhazardous material (except Metallic powder)

Marine Pollutant Not applicable

Airlines restriction Nonhazardous material (except Metallic powder)

Security precaution

It is necessary to note it for handling because the tip of the blade and the getting injury are received.

Prevent collapse of cargo at the time of transportation.

15. REGULATORY INFORMATION

- Pollutant Release and Transfer Register (PRTR)
- Industrial Safety and Health Act

16. SPECIAL PRECAUTION

Al information, recommendations and suggestions contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made by AMADA CO.Ltd. with respect to the information provided.

Employers should use this information only as a supplement to other available data.

<reference> METI web site : http://www. meti. go. jp/

MOE web site : http://www. env. go. jp/
MHLW web site : http://www. mhlw. go. jp/
ICSC card : http://www. nihs. go. jp/ICSC/

NITE web site : http://www.nite.go.jp/

(Chemical information)

JISHA web site : http://www.jaish.gr.jp/

(GHS model label model SDS information)

Japan Society for Occupational Health web site: https://www.sanei.or.jp/

(Working environment (Japan Society for Occupational Health acceptable concentration))

XThis SDS is made suitable only for Japan's market and subject to the laws of Japan.

If you would like similar information for overseas, please contact info.machinetools@amada.co.jp.